

System Capacity

			KX-TDA600			
			Basic System	2 Shelf System	3 Shelf System	4 Shelf System (Max)
Extensions	Max Extension Port (DPT and DSL)	Without DXDP*	160	320	480	640
		With DXDP*	240	480	720	960
	Single Line (a/b) Telephone (SL)		160	320	480	640
	Digital Proprietary Telephone (DPT)	With/Without DXDP*	160	320	480	640
	(Type 1) Note 1, Note 3					
	Digital Proprietary Telephone (DPT)	(Type 2) Note 2	128	256	384	512
	Analogue Proprietary Telephone (APT)		80	160	240	320
Direct Station Select (DSSS) Console		64	64	64	64	
Voice Processing System (VPS)		8	8	8	8	
Trunks	Trunk Port		160	320	480	640
	ISDN Trunk	BRI	160	320	480	640
		PRI	150	300	450	600
	Analogue Trunk		160	320	480	640
	IP-Gateway		160	320	480	640
Wireless	Portable Station (PS)	Without Memory Expansion Card	256	256	256	256
		With Memory Expansion Card	512	512	512	512
	Cell Station (CS)		32	64	96	128
Doorphone Port			16	32	48	64
PC Console			8	8	8	8
PC Phone			128	128	128	128



Line-up KX-TDA600 and the optional Expansion Kit KX-TDA620 (3 + TDA600)

*DXDP: Digital eXtra Device Port
 (Note 1): Type 1: T7600, T7560, T7565 Digital Proprietary Telephones
 (Note 2): Type 2: Current Digital Proprietary Telephones (T7200, T7500 series)
 (Note 3): Max number of DPT extension channels = 160 per system. DXDP does not increase system capacity over this amount, only reduces the number of cards required.

Option List for TDA600

	Model	Description
Cabinet	KX-TDA600 (Proprietary)	Basic Shelf (Main Unit)
	KX-TDA620 (Proprietary)	Expansion Shelf Bus Slave Connection Circuit added initially (BS)
Power Supply	KX-TDA0103	Large Power Supply Unit (L-PSU)
	KX-TDA0104	Medium Power Supply Unit (M-PSU)
EMPR	Daughter cards for EMPR card only	Memory Expansion Card (EMEC)
	KX-TDA0105 KX-TDA0196	Remote Card (RMT)
Inter Connection	KX-TDA6110	Shelf Connection Card for Base Shelf (BUS M)
	KX-TDA6111	Additional Card for connecting Expansion Shelf 2 and 3 (BS ME) Mounted onto Bus M Card
Extension Cards	KX-TDA0170	8-Port Digital Hybrid Extension Card (DHL8C)
	KX-TDA0171	8-Port Digital Extension Card (DLC8)
	KX-TDA0172	16-Port Digital Extension Card (DLC16)
	KX-TDA0173	8-Port Single Line Telephone Card (SL)
	Daughter card for SLC8 card only	8-Port Analogue Extension Caller ID card (EXT-CID8)
	KX-TDA6174	16-Port Single Line Telephone Card (ESL16)
	KX-TDA6175	16-Port Single Line Telephone Card with Message Lamp (EMSL)
	KX-TDA0470	16-Port IP PT Extension Card (IP-EXT16)
	KX-TDA6181	16-Port Analogue Trunk Card (ELOT16)
	Daughter cards for LCOT cards only	8-Port Caller ID/Pay Tone Card (COT8)
Trunk Cards	KX-TDA0182	8-Port Caller ID Card (CID8)
	KX-TDA0184	8-Port Direct Dialling In (DID) Card (DID8)
	KX-TDA0188	8-Port E&M Trunk Card (E&M8)
	KX-TDA0284	E-Trunk Card (E1)
	KX-TDA0288	4-Port Basic Rate Interface (BRI) Card (BRI4)
	KX-TDA0290	8-Port Basic Rate Interface (BRI) Card (BRI8)
	KX-TDA0480	Primary Rate Interface (PRI) Card (PRI 30)
	KX-TDA0484	4-Channel VoIP Gateway Card (IP-GW4)
	KX-TDA0490	4-Channel VoIP Gateway Card (IP-GW4E)
	KX-TDA0141	16-Channel VoIP Gateway Card (IP-GW16)
	KX-TDA0142	2-Channel Cell Station Unit for DHL8C/DLC Card
	KX-TDA0143	4-Channel Cell Station Unit for CS16C
	KX-TDA0144	4 Cell Station Interface Card (CS16) TDA0142
	KX-A272	8 Cell Station Interface Card (CS16) TDA0142
	Option Cards	KX-TDA0190
KX-TDA0410		Optional 3-Port Base Card (OPB3)
KX-TDA6166		CTI Link Card (TAPI/CS7, 10Base-T)
KX-TDA0161		16-Channel Echo Cancellation Card (ECHO16)
Daughter cards for OPB3 card only		4-Port Doorphone Card (for KX-T30865) (DHP4) 2-Port Doorphone Card (for German Type) (DPH2) 4-Port External sensor Card (EIO4) 4-Channel Message Card (MSG4)
Other	KX-TDA6920	SD Card containing Enhanced Feature Upgrades
	KX-TDA6201	Mounting Kit - Contains 4 Wall Mounting Plates, 4 Screws, and 4 Nuts

Specifications

KX-TDA600
Power Voltage: AC100V ~ 240V
External Battery: +36V (+12V x 3) Built-in interface
Memory Back-up Duration: 7 years
Dialling: Extension - DP (10pp80pps)DTMF CO - DP (10pp80pps)DTMF
Mode Conversion: DP-DMF, DTMF-DP
Connectors: CO Line - Amphenol Connector Station - Amphenol Connector Paging Output - 2 conductor jack External Voice Output - 2 conductor jack
Ring Frequency: 20/25 Hz (Selectable)
Central Office Loop Limit: 1600 ohms Max.
Operating Environment: Temperature - 0 - 40 C (32 - 104 F) Humidity - 0 - 90%
MOH (Music on Hold): 2 ports MOH # 1 External Music Source MOH # 2 Internal Music / External Music Source (Level control: -6dB ~ +6dB@3dB)
Internal Paging: Level control: -6dB ~ +6dB@3dB
External Paging: 2 ports (Level control: -15dB ~ +15dB@3dB)
Serial Interface Port: USB port RS-232C port (115.2kbps)
Structure: Free Slot style Can be accommodated into 19" CR

System Feature Capacity

		KX-TDA600
System	Tenant	8
	Class of Service	64
	Trunk Group	96
	User Group	96
	Paging Group	96
	Call Pickup Group	96
	Incoming Call Distribution (ICD) Group	128 groups, 128 extensions per group
	Portable station (PS) / Trunk Group	32
	Voice Mail (DTMF) Group	8
	Voice Mail (DTMF) Group	8
	Queueing Time Table	128
	Idle Extension Hunting Group	128 groups (16 extensions per group)
	Absent Message (System / Extension)	8 message x 16 characters per system 1 message x 16 characters per extension
	Message Waiting	1672 (1032PT+SL) + (640ICDG+PS)
	Number of the characters of Name	20
	Extension Number Digits	5 digits
	Call Park Zone	100
	Conference	3x10 - 8x4 per shelf
	Special Carrier Code	16 digits, 100 entries
	Verified Code	4 digits x 1000 entries
	Verified Code Personal Identification Number (PIN)	10 digits, 1000 entries
	Host PBX Access Code	10 digits (10 entries / trunk group)
	DDI/DID Table	32 digits (1000 entries)
Station Message Aided Recording (SMDR) Call Storage	1000 calls w/o EMEC 4000 calls w EMEC	
Toll Restriction / Barring	Toll Restriction/Barring Level	7
	Toll Restriction /Barring Denied Code	16 digits, 100 entries per level
	Toll Restriction /Barring Exception Code	16 digits, 100 entries per level
Networking	TIE Routing Table	32 entries
	Leading Number	3 digits
	PBX Code	7 digits

		KX-TDA600
Automatic Route Selection (ARS)	Routing Plan Table	48 entries
	Leading Number Table	16 digits, 1000 entries
	Leading Number Exception Table	16 digits, 200 entries
Dialling	ARS Carrier	48
	Itemised Billing Code	10 digits
	Authorisation Code	10 digits
	Emergency Call	32 digits, 10 entries
	Quick Dialling	4 digits, 80 entries w/o EMEC 4 digits, 80 entries + 8 digits 1000 entries w EMEC
	System Speed Dialling	32 digits, 1000 entries per system w/o EMEC 32 digits, 1000 entries per Tenant w EMEC Max: 8 Tenants
	Personal Speed Dialling	32 digits, 10 entries per extension w/o EMEC 32 digits, 100 entries per extension w EMEC
	One-Touch Dialling	32 digits
	Hot Line	32 digits
	Key Pad Protocol Dial (ISDN Voice Access)	32 digits
Password	Redial	32 digits
	System Password for Administrator	4-10 digits
	System Password for User	4-10 digits
	Manager Password	4-10 digits
Voice Mail	Extension Personal Identification Number (PIN)	0-10 digits / extension
	Max Number of VPS Systems	8
	Max Number of VPS Channels	8 x 24ch
Call Log	Outgoing Call Log	10 logs per extension 5 x 1152 logs per system 100 logs per extension 10 x 1280 logs per system
	Incoming Call Log	

Feature List

System Features

- Automatic ISDN Setting (BRI)
- Automatic Route Selection (ARS) / Least Cost Routing (LCR)
- Background Music (BGM)
- Budget Management
- Busy on Busy
- Call Park with Indication
- Call Pickup Group
- Call Distribution by Caller ID
- Class of Service (COS)
- CTI (CSTA, TAPI)
- Data Line Security
- Delayed Ringing
- Direct In Lines (DIL)
- Direct Inward Dialling (DID)
- Direct Inward System Access (DISA)
- Door-Phone / Door Opener
- Echo Cancellation
- Extension Lock
- Emergency Call
- Existing APT / DPT Compatibility
- External BGM
- Flexible Numbering Plan (4-digits)
- Floating Extension
- Greeting Message
- Host PBX Access Code
- Hunting Group
- Hurry-Up Transfer
- Incoming Group (Hunting Group)
- Intercept Routing - Busy / DND
- Intercept Routing - No Answer
- Intercept to Trunk
- Line Monitor (CO)
- Main Processing Card (MPR) / CS Software Download
- Manager Functions
- Multiple Language Support
- Online Diagnostics
- Operator Functions
- PC Console / PC Phone
- PC Programming
- Paging Group
- Quick Set-up
- Remote Alarm Notification
- Remote Extension Status Control through DISA
- Remote Extension Lock
- Ring Group
- Special Carrier Access
- Station Message Detail Recording (SMDR)
- SMDR 12 and 24 Hour Time Format
- SMDR Caller ID Printing
- System Memory Expansion
- Tenant Service
- Timed Reminder
- Time Service (Day/Night/Lunch/Break)
- Toll Restriction
- Trunk Group
- Uniform Call Distribution (UCD)
- User Group
- VIP-Call
- Visual Caller ID

<Voice Mail (VM) Features>

- Automatic Configuration - Quick Setup
- Call Forwarding to VM
- Caller's Identification Notification to VM
- Intercept Routing to VM
- LCD for VM operation
- Live Call Screening (LCS)
- Remote PBX Data Control by VM
- VM Data Control by PBX
- VM (Digital / DTMF) Integration
- VM Group
- VM Mail Transfer
- VM Message Number display on DPT LCD

Extension Features

- 4-Party Conference with Broadcasting up to 32-Party
- Absent Message
- Account Code Entry (Forced)
- Automatic Redial
- Boss - Secretary
- Broadcasting
- Caller ID to SLT
- Call Forwarding (All Calls, Busy, Busy/No Answer, No Answer, Follow Me, From Incoming Group)
- Call Hold
- Call Pick-up (Directed, Group, DSS, Deny)
- Call Transfer (Screened, Unscreened, One-Touch Transfer, Transfer Recall)
- Conference (3-Party Conference, Multi Party conference, Unattended Conference)
- Dial Type Selection
- Digital Duplex Speaker Phone (SP-phone)
- Digital eXtra Device Port (DXDP)
- Direct One-Touch Answering
- Do Not Disturb (DND)
- DSS Console
- Executive Busy Override
- Extension Directory
- Extension-to-Trunk Call duration Time
- External Feature Access
- Flexible Buttons
- Hands-free Operation
- Handset / Headset Selection
- Large Telephone Display Features with Back-lit
- LED control for CTI
- Log-In / Log-Out
- Message Waiting
- Multi-Lingual Display
- Multiple Hop Call Forwarding (4 steps)
- Music on Hold
- Off-Hook Call Announcement (OHCA)
- Off-Hook Monitor
- One-Touch Dialling
- Paging (Deny, Paging Transfer)
- Paralleled Telephone (APT/DPT & SLT, DPT/SLT & PS)
- Redial, Last Number
- Remote Station Control
- Speed Dialling - Personal & System
- Time and Date Display
- Tone Pulse Conversion

- Trunk Answer from Any Station (TAFAS)
- Walking Class Of Service (COS)
- Whisper OHCA (Off-Hook Call Announcement)
- Wrap-Up
- eXtra Device Port (XDP)

<DECT Features>

- Automatic Handover
- DECT CS on Digital Extension Port
- Headset Compatibility
- Incoming & Outgoing Call Log
- LCD Control via CTI*
- Wireless XDP Parallel Mode
- Vibrator Ring (KX-TCA255 Only)

ISDN Service Features

- Advice of Charge (AOC)
- Calling Line Identification Restriction (CLIR)
- Calling Line Identification Presentation (CLIP)
- Completion of Calls to Busy Subscriber (CCBS)
- Connected Line Identification Presentation (COLP)
- Connected Line Identification Restriction (COLR)
- Direct Dialling Inward (DDI)
- ISDN 3 Party Conference (3PTY)
- ISDN Call Forwarding (CFU / CFNR / CFB)
- ISDN Call Transfer (CT)
- ISDN Extension
- Malicious Call Identification (MCID)
- Multiple Subscriber Numbers (MSN)

Networking Features

- Alternated Routing
- ARS with VoIP
- DISA Call to the Network
- Network Busy Lamp Field (BLF)*
- Network Closed Numbering
- Private Network to Public Network
- Public Network to Private Network
- QSIG Connection
- Tandem Connection
- Transfer to Network PBX
- Virtual Private Network (VPN)
- VoIP Network (Built-in IP-GW)

* Optional software required

DPT: Digital Proprietary Telephone
APT: Analogue Proprietary Telephone
SLT: Single Line Telephone
PS: Portable Station

Design and specification subject to change without notice e. ME0809-008-TDA600. Printed in the UK.

